

IN THE SPECIFICATION:

Please replace the paragraph beginning on page 8, line 29, with the following rewritten paragraph:

B¹
Pressure sensor 10, which is located in hydraulic unit 9, which is filled with hydraulic fluid, is connected to a display and/or driving device 1 by a computer integrated into the control unit 16, turning the device off on reaching or exceeding a definable limit value. This reliably limits the maximum pressure head in the entire system in the event of a blockade of hydraulic unit 9 or a defect in the valves or clamps of the head piece, for example.

IN THE CLAIMS:

Please cancel claims ~~31~~ and ~~32~~ without prejudice.

Please amend claims 20 and 35 as follows:

B²
20. (amended) A pumping device for delivering and metering medical fluids comprising:

- a. a membrane unit having a membrane bordering a first chamber;
- b. a pumping unit connected to the first chamber by a hydraulic unit containing hydraulic fluid that is in fluid connection with the first chamber;
- c. a hydraulic sensor in fluid connection with the hydraulic unit, the hydraulic sensor adapted and arranged for measuring the pressure of the fluid within the hydraulic unit;
- d e. a measuring device for measuring the pumping unit output; and
- e d. a control unit connected to the measuring device, ~~and~~ the pumping unit, and the hydraulic sensor; wherein the control unit is adapted and arranged for controlling the pumping unit output based on the measurements of the measuring